

ASPHALT CRACKFILLER COATING

EXTREMELY DURABLE, ASPHALT CRACKFILLER, PREMIUM SEALER COATING IN ONE.



Specially formulated, ready to use, high performance, PREMIUM quality Asphalt Crack Filler Coating Sealer. This is **not** a low-quality big box store coating. It is a well formulated, well tested premium quality asphalt emulsion fortified with acrylic latex and rubber polymers. It contains special aggregates to give a tough, non-skid, water proof, flexible surface.

Priced by the gallon. Packaged in 5, 55 or 250-gallon containers.



This well formulated, thoroughly tested **premium quality asphalt coating, black-top seal coating supplied as ready to use.** No thinning or addition of sand or aggregate is needed. Just blend the product thoroughly and apply. It is **fortified with special acrylics, rubber polymers and aggregates to yield a strong durable, anti-skid, flexible water-proof asphalt coating-sealer.** It can be applied over 1-inch thick wide cracks. This coating will cure over-time and will not crack and will stay flexible. Two coats may be needed in certain applications. Severely damaged and cracked asphalt can be repaired and protected. Being water based it is non-flammable, non-toxic. Dries fast and will not track. Depending on job requirements and budget, we offer several grades of Asphalt Sealers-overlays-coatings.

- **High performance crack-filler and asphalt sealer in one product.**
- Formulated and tested to repair severely damaged, neglected, cracked asphalt.
- Saves the time and expense to completely remove and reinstall asphalt surfaces.
- Will rejuvenate, water-proof, protect for years of service.
- Expensive. But its long-term performance and durability far outweigh the product cost.
- Ready to use. Will not excessively settle in shipping or storage.
- No need to add sand or aggregate. Ready to use.
- Based on Safe Asphalt emulsion. Will not smell, burn or irritate skin.
- Fortified with high percentage of Acrylic Latex and Rubber polymers for extra durability and flexibility.
- **Will resist reflective cracking and water deterioration.**
- Dries fast at 77°F will not wash away even if it rains 1 hour after application.
- Can be sprayed or applied with roller or with a squeeze at temperature range of 40 - 90°F.
- We offer several grades of asphalt sealers depending on the job requirements and budget.