

LITHIUM CONCRETE COATING- CoSi

PERMANENT, TOUGH, DURABLE, SILICATE CHEMISTRY CONCRETE MASONRY COATING.



Inorganic silicate concrete coating specifically formulated to form an extremely strong permanent chemical bond with concrete substrates. COATING version designed to be thicker with better hiding for use as a top coat. Application is similar to conventional coatings but ingredients in **COATING CoSi** are designed to react with lime in concrete to form an extremely strong bond resulting in a superior, very durable, extremely tough, permanent protective coating.

Priced by the gallon. Packaged in 5- or 55-gallon containers.



Rejuvenate, beautify and protect a variety of concrete substrates **extremely durable, tough, inorganic coating based on a unique silicate chemistry.** **COATING CoSi** coatings are designed to be thicker with better hiding power than stains. **COATING CoSi** chemically bond with the lime in concrete to form calcium silicate hydrate structure. This bonding reaction occurs during curing of concrete and that gives concrete its mechanical and structural strength. Designed to have the same reaction between **COATING CoSi** inorganic coating and concrete substrate, **resulting in an incredibly tough, extremely hard, permanent, durable concrete coating.**

- **Thicker and better hiding power than stains for better coverage.**
- Water based, non-flammable, Eco friendly, high solids, Low VOC's,
- Extremely Durable, incredibly Tough with good abrasion, scratch and water-resistance.
- **COATING CoSi forms a strong calcium silicate permanent chemical bond with concrete.**
- This is NOT AN acid etching stain, that can degrade the concrete substrate.
- Unique formulation that becomes integral part of concrete. Guaranteed for 25 years.
- **COATING CoSi** is designed to cover small cracks and imperfections on concrete masonry surfaces.
- DO NOT apply on painted surfaces. Designed to react with concrete surface.
- Cured coating is breathable, allows vapors to escape preventing peeling.
- Easy to use. Similar to conventional water-based stains, paints and coatings.
- **Available in 10 standard colors, Custom color matching if needed,**
- Dries, Cures fast 1-3 hours, no prolonged down times.
- Can be applied on most clean, sound concrete masonry substrates, including pre-cast.