

SUPREME SB



ACRYLIC-ALKYD EXTREMELY DURABLE PARKING, HIGHWAY, AIRPORT RUNWAY PAINT.

Uniquely formulated this one component, fast dry, solvent based, **extremely durable, tough paint**, performs far better than any one component traffic paint. Its performance is equal to or exceeds that of traditional chlorinated rubber traffic paints. **Use as high-performance line marking striping paint for streets, roads, parking garages, highways, airport runways.**

Priced by the gallon. Packaged in 5-gallon metal pails.

SUPREME is a high performance, high solids, extremely durable acrylic-alkyd co-polymer solvent-based paint. It dries quickly to a hard, extremely durable finish even in humid cold conditions. The viscosity is adjusted to a spray consistency and is ready to use, thinning is not required or recommended. **Apply SUPREME with a synthetic bristle brush, synthetic roller and low-pressure air-less spray striping equipment designed to handle solvent based paints.** **SUPREME paint is designed to be applied to as much as a 30-mil wet thickness each pass in two passes. Glass beads can also be added for more reflectivity.** **SUPREME** can be top-coated with a clear coat for extra longevity and performance. Clean-up of striping machine and uncured paint is done with paint thinner. A Technical Coatings spec alkyd acrylic used for striping asphalt and concrete.

For parking lots, parking garages, side streets, curbs were dry time is not a issue, this grade is an excellent choice. It has good hiding power, good overage, contains high solids and low VOCs. It contains some acetone to reduce the VOC'S. Being a solvent based paint, it is flammable. It is good for most substrates, except new asphalt and freshly applied seal coating. Its exterior durability, bead retention, abrasion resistance and adhesion to substrate, is good.

- Unique, specially formulated polymeric binder system with the right pigments make it extremely durable.
- **Available in White, Yellow, Blue, Black and Red.**
- **High Solids, Acceptable VOC,**
- Good coverage. 400 lineal feet per gallon when applied 4-inch-wide stripe.
- Quick Dry times. 30 mins. to foot, 45 mins. to car traffic.
- Can be applied with conventional airless spray machines that can handle solvent based paints.
- Caution: Flammable, not for use on freshly applied asphalt or seal coating