

# TTP 115 TYPE II



## **FAST DRY, CO-POLYMER RESIN, SOLVENT BASED, TRAFFIC LINE MARKING PAINT.**

Pavement line striping paint, fast dry, excellent performance that meets the Federal Specification **TTP-115 Type II** for top performing solvent-based traffic line marking paints. This traffic paint is designed to dry fast, easy to apply, forms a very durable, weather resistant, reflective coating, Ideal for striping, painting traffic line marking on city streets, roads, highways, cross walks, legends and sign markings on streets. Airport runway line marking paint.

*by the gallon. Packaged in 5-gallon metal buckets, 55-gallon drums.*

**TTP-115 Type II is a high performance, high solids, extremely durable acrylic-alkyd co-polymer solvent-based paint.** It dries quickly to a hard, extremely durable finish even in humid cold conditions. The viscosity is adjusted to a spray consistency and is ready to use, thinning is not required or recommended. Apply **TTP-115 Type II** with a synthetic bristle brush, synthetic roller and low-pressure air-less spray striping equipment designed to handle solvent based paints. This formula can be applied to as much as a 30-mil wet thickness each pass in two passes. Glass beads can also be added for more reflectivity. It can be top-coated with a USSC clear coat for extra longevity and performance. **Clean-up of striping machine and uncured paint is done with paint thinner. For use as a high-performance traffic line paint on parking lots, parking garages, streets, roads, highways and airport runway marking paint. It has good hiding power, good overage, contains high solids and low VOCs.** It contains some acetone to reduce the VOC'S. Being a solvent based paint, it is flammable. It is good for most substrates, except new asphalt and freshly applied seal coating. Its exterior durability, glass bead retention, abrasion resistance and adhesion to substrate, is excellent.

- **Available in White, Yellow, Blue, Black and Red.**
- High Solids, Acceptable VOC.
- Good coverage. 400 lineal feet per gallon when applied 4-inch-wide stripe.
- Quick Dry times. 30 mins. to foot, 45 mins. to car traffic.
- Can be applied with conventional airless spray machines that can handle solvent based paints.
- Caution: Flammable, not for use on freshly applied asphalt or seal coating.